
imageRUNNER C1225iF

Productive and cost effective A4 colour multifunctional

The imageRUNNER C1225iF is a feature rich A4 colour multifunctional device, providing fast and efficient document handling 'out of the box' so you can focus on your business priorities.





- Powerful A4 colour multifunctional with print, copy, colour scan, send and fax functionality, ideal for demanding small businesses
- Simple and user friendly operation with the 8.9 cm colour touch and swipe LCD display
- Canon's V² colour (Vivid and Vibrant) imaging technology ensures documents impress and stand out from the rest
- Seamlessly fits into your office environment with network connectivity and supporting IT standards such as PCL and Genuine Adobe PS
- Increase productivity with up to 1,100 sheet capacity and a Duplex Automatic Document Feeder (DADF)
- Scan and Send documents directly to a variety of destinations including email and shared folder

- Flexible mobile printing and scanning capabilities such as Apple AirPrint™, Mopria printing as well as mobile printing and scanning apps, support mobile worker efficiency
- Out of the box easy install; users can access the set-up guide via the user interface
- Consumables can be changed easily reducing down-time
- Standard toner included in the box giving up to 12 months colour printing¹
- Giving you peace of mind with Canon's standard warranty
- Energy consumption as little as 1 watt in sleep mode
- Compact and efficient space saving design









FA







Technical Specifications

imageRUNNER C1225iF

Machine type Available core functions

Printer Specifications

Print speed (BW/Colour)

Printing method Print resolution Double sided printing **Direct print**

Printing from mobiles or internet-connected devices and cloud-based services Paper input (Standard)

Paper input (Option) Maximum paper input capacity

Paper output capacity Finishing capabilities Supported media types

Supported media sizes

Supported media weights

Page Description Language(s) Fonts

Operating System compatibility

Copy Specification

Copy speed (BW/Colour) First Copy Output Time (FCOT) (BW/Colour) Copy resolution

Multiple copy Reduction/Enlargement

Scan Specification Ontional/Standard

Supported media size/s

Supported media weight/s

Colour A4 Laser Multifunctional (Reader / Printer standard) Print, Copy, Scan, Send and Fax standard for C1225iF

25/25ppm (A4 Single-sided), 26/26ppm (A5 Single-sided), 25/25ppm (A4 Double-sided), 26/26ppm (A5 Double-sided) Colour Laser Beam Printing

2400 dpi equivalent x 600 dpi, 600 dpi x 600 dpi

Automatic (Standard)

Direct printing available from USB memory key Supported file types: JPEG, TIFF, PDF

A range of software is available to provide printing from mobile or internet-connected devices. Please contact your sales representative for further information.

1 x 550-sheet (80 gsm) cassette, 100-sheet (80 gsm) multi-purpose trav

1 x 550-sheet cassette (80 gsm) (Cassette Feeding Unit-AJ1) 1200 sheets (80 gsm)

250 sheets (80 gsm) Standard: Collate, Group

<u>Cassette/s:</u> Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelopes*
*Envelope support via standard cassette 1 only.

Multi-purpose tray:
Thin paper, Plain paper, Recycled paper, Colour paper, Heavy
paper, Pre-punched paper, Transparency, Labels, Envelopes
(No.10 (COM10), Monarch, ISO-C5, DL)

<u>Paper cassette 1:</u>
Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes (No.10 (COM10), Monarch, DL)
Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm)

<u>Paper cassettes 2:</u> Standard size: A4, A5, B5, Legal, Letter, Executive, Statement Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm)

Multi-purpose tray: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (98.4 mm to 216 mm x 148 mm to 355.6 mm), Envelopes (No.10 (COM10), Monarch, ISO-C5,DL)

Cassette/s : 60 to 163 gsm Multi-purpose tray: 60 to 220 gsm Duplex: 60 to 163 gsm

UFRII , PCL5c/6, Adobe PostScript Level 3 (Standard for C1225iF)

PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts PS fonts: 136 Roman fonts

UFRII: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later)

PCL: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2

PS: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows8/Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later)

PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows XP / Windows Vista / Windows 7 / Windows 8/ Windows 8.1

Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.

SAP Device Types are available via the SAP Market Place.

Please refer to the quoted print speeds

8.4 sec / 10.5 sec

Reading: 600 dpi x 600 dpi Printing: 600 dpi x 600 dpi

Up to 999 copies 700m: 25 - 400 % in 1 % increments

Fixed Zoom Ratio: 25%, 50%, 70%, 100%, 141%, 200v%, 400%

Standard on all models (DADF 50 sheets)

A4, A5, B5, Custom sizes: 140 mm to 216 mm x 128 mm to 356 mm (when fed through the DADF)

Single-sided scanning: 50 to 105 gsm (DADF) Double-sided scanning: 64 to 105 gsm (DADF)

Scan resolution

Scan methods

Double sided scanning

<u>BW Scan:</u> 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi

CL Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi 2-sided to 2-sided (Automatic)

BW single-sided: 25 ipm (A4, 300 dpi X 300 dpi), BW double-sided: 9 ipm (A4, 300 dpi X 300 dpi) CL single-sided: 25 ipm (A4, 300 dpi X 300 dpi), CL double-sided: 9 ipm (A4, 300 dpi X 300 dpi),

Push Scan: Colour Send functionality is standard. Pull Scan: TWAIN/WIA Pull scanning available on all models.

Pull Scan: I WAIN/WIA Pull scanning available on all models. Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices: A range of solutions is available to provide scanning to mobile devices, internet-connected devices depending on your requirements. Please contact your sales representative for further information.

Pull scan specifications TWAIN/WIA Pull scanning

Windows XP

Windows Vista/Windows 7/Windows 8/Window8.1

Mac Scan (TWAIN only) Mac OS X 10.5.8 or later

*The drivers are available via http://software.canon-europe.com

Send Specifications

Optional/Standard Send resolution

Destinations Address Book/Speed dials

File formats

Optional Universal Send

Optional/Standard

Modem speed Fax resolution

Fax memory Speed dials Group dials / destinations Sequential broadcast Memory backup

Other features

General Specifications

Warm-up time Recovery from sleep mode Interface type

Network protocols

Memory Control panel Dimensions (W x D x H)

Installation space (W x D)

Weight

Operating environment

Power source Power consumption Standard on all models

100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi E-Mail, Fax (not available for C1225), PC (SMB, FTP)

LDAP (Max. 50 searchable), Local (Max. 300 including 281 Speed dials)

SMB: JPEG, TIFF, PDF, Compact PDF, Searchable PDF E-mail: PDF, Compact PDF, Searchable PDF

Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files

Standard for C1225iF

Super G3 33.6 kbps (Up to 3 seconds per page¹)

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages

Max. 281 Max. 199 dials

Max. 310 addresses

Fax Forwarding, Dual Access, PC Fax (TX only)

Approx. 34 seconds from power ON

10 seconds or less

USB 2.0 Hi-Speed,1000BaseT / 100Base-TX / 10Base-T, 1 x USB Host (Front), 1 x USB Host (Rear), 1 x USB device Recommended third party wireless solution is Silex SX-BR-4600 WAN. For more details please refer to www.silex-europe.com TCP/IP* (LPD / Port 9100 / WSD / IPP / IPPS / SMB / ETP).

IPX/SPX (NDS, Bindery)
*IPv4/IPv6 support

1.0 GB

QVGA Color LCD 8.9 cm (3.5 inch) touch / swipe

supported display Standard: 511 mm x 549 mm x 610 mm

With Cassette Feeding Unit-AJ1: 511 mm x 549 mm x 1035 mm

852 mm x 843 mm (Main unit + Multi-purpose tray open + Cassette drawers open)

Approx. 44 kg including toner Temperature: 10 to 30°C (50 to 86°F)

Humidity: 20 to 80 % RH (no condensation) 220 - 240 V (±10 %), 50/60 Hz (±2 Hz), 3.7 Amp

Maximum: Approx 15 KW Maximum: Approx. 1.5 KW Standby: Approx. 3.0 W Sleep mode: Approx. 1.0 W or less ² Time to put the device to sleep mode: 60 sec Typical Electricity Consumption (TEC) rating ³: 0.8 kWh

Only for C1225 (non Fax model) Plugin-off: 0.5W or less (Normal mode) Time to put the device to plugin-off: 4 hours



Technical Specifications

imageRUNNER C1225iF

Noise levels Sound Pressure ⁴ (reference data, LpAm, Bystander's position)

Software and printer

Security features

Toner bottle

Sound Pressure Noise Levels: Active: 50 dB Standby: Inaudible (Less than 30dB)

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables

services such as meter capture, automatic consumables management and remote diagnostics.

Remote Firmware System (GDLS):

Allows the remote distribution of firmware.

Remote User Interface (RUI): Web-based interface to each device that helps to provide remote device management

Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers

Standard:

Jaridard.
IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Secured Print, Department ID
Optional: Send PDF Security Feature Set-E1@E

Toner 34 Black / Cyan / Magenta / Yellow Toner (Yield: BK 12,000 / CMY 7,300 pages) ⁵

Specifications for options

Cassette feeding unit

Hardware accessories 1

Document security

Print controller accessories

Name: Cassette Feeding Unit-AJ1
Description: Optional cassette feeding unit with 1 x 550 sheets
paper capacity. Takes the cassette paper capacity up to 1,200
sheets. Dimensions (W x D x H): 511 mm x 508 mm x 425 mm Weight: Approx. 15 kg

HANDSET-J1 EUR/HANDSET-J1 SA

BARCODE PRINTING KIT-D1@E: Enables barcode printing via jet caps technology.

Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files.

Drum Unit 034 (BK / C / M / Y) Waste Toner Box WT-A3:

Other options

Pased on ITU-T Standard Chart No. 1

1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information

³ Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (http://www.eu-energystar.org).

⁴ Declared noise emission in accordance with ISO 7779

5 Based on 5% coverage (A4)

All specifications subject to change without notice



iRC1225iF 511 mm x 549 mm x 610 mm



Cassette Feeding Unit-AJ1

























Canon Inc. canon.com Canon Europe canon-europe.com **English** edition © Canon Europa N.V.,2014

Canon (UK) Ltd Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000 Facsimile 01737 220022 canon.co.uk

Canon Ireland 3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525



•

Productive and cost effective A4 colour multifunctional

The imageRUNNER C1225iF is a feature rich A4 colour multifunctional device, providing fast and efficient document handling 'out of the box' so you can focus on your business priorities.

Sales Start Date: March 2015

imageRUNNER C1225iF



Product Details:

Product Name	Mercury Code	EAN Code	
imageRUNNER C1225iF	9548B007AA	4549292024654	

Optional Accessories:

Consumables	Mercury Code	EAN Code
Toner 034 Black	9454B001AA	4549292017106
Toner 034 Cyan	9453B001AA	4549292017090
Toner 034 Magenta	9452B001AA	4549292017083
Toner 034 Yellow	9451B001AA	4549292017076
Drum Unit 034 Black	9458B001AA	4549292018059
Drum Unit 034 Cyan	9457B001AA	4549292018080
Drum Unit 034 Magenta	9456B001AA	4549292018073
Drum Unit 034 Yellow	9455B001AA	4549292018066
WASTE TONER BOX WT-A3	9549B002AA	4549292029123
Network	Mercury Code	EAN Code
Barcode Printing Kit-D1@E	3999B005AA	N/A
Send/Fax	Mercury Code	EAN Code
Send PDF SECURITY Feature Set -E1@E	9594B002AA	N/A
HANDSET-J1 EUR	2821B003AA	4960999575698
HANDSET-J1SA	2821B005AA	4960999575711
Paper Supply	Mercury Code	EAN Code
CASSETTE FEEDING UNIT-AJ1	9579B001AA	4549292028836



.

imageRUNNER C1225iF

Productive and cost effective A4 colour multifunctional

The imageRUNNER C1225iF is a feature rich A4 colour multifunctional device, providing fast and efficient document handling 'out of the box' so you can focus on your business priorities.



Measurement / Logistic Information:

Product Name	Mercury code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Net Weight (Kg)	Gross Weight (Kg)
imageRUNNER C1225iF	9548B007AA	EP	Euro Pallet	1	626	720	847		45.5 kg

What's in the box?

- Main Unit
- 4 toner bottles (BK / Y / M / C)
- Getting Started Guide
- Warranty Card
- User Software DVD
- Power Cable

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2014 Canon (UK) Ltd Woodhatch Reigate Surrey RH2 8BF Telephone no 01737 220000 Facsimile 01737 220022 canon.co.uk Canon Ireland 3006 Lake Drive Citywest, Saggart Co.Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525

